

ENERGY AUDITOR - 2019 Field Guide

March 1, 2019

Standards of Reference: Section 9 of the Energy Auditor Scheme Handbook

Exterior

- 1. (GATED ITEM) Candidate prepared combustible gas and CO measurement instruments for use
- 2. Candidate displayed ability to accurately measure perimeter of the home within 10% accuracy, or building section identified by proctor
- 3. Candidate identified the exterior cladding material(s)
- 4. Candidate identified or discussed possibility of lead-based paint
- 5. Candidate identified existing moisture issue(s) or potential moisture problems in general that have a negative impact on a home
- 6. Candidate identified roof exposure and orientation
- 7. Candidate identified roof condition, materials, penetrations, and unusual features
- 8. Candidate identified condition of roof flashing and gutter system
- 9. Candidate provided a preliminary identification of the thermal boundary based on exterior inspection
- 10. Candidate summarized findings of exterior inspection of the building

Interior Safety Evaluation

- 1. (GATED ITEM) Candidate tested indoor ambient CO levels and compared results to current version of ANSI/BPI-1200
- 2. (GATED ITEM) Candidate tested indoor ambient air and verbally confirmed that combustible gases are below 10% of LEL on each floor
- 3. Candidate located existing smoke and CO detectors
- 4. Candidate identified or discussed mold or conditions that could promote the growth of mold
- 5. Candidate identified or discussed electrical hazards
- 6. Candidate identified or discussed signs of pest or vermin infestation
- 7. Candidate accurately assessed clothes dryer vent configuration
- 8. Candidate identified or discussed other safety concerns

Interior Safety Evaluation (con't)

- 9. Candidate conducted combustion gas leak testing according to current version of ANSI/BPI-1200 for 1-2 minutes and on at least 3 fittings
- 10. Candidate recommended leak detection solution to verify positive reading from detector

Doors and Windows

- 1. Candidate identified door material and features such as approximate R-value, fire rating, and glazing
- 2. Candidate evaluated door performance
- 3. Candidate identified if door repairs needed
- 4. Candidate identified if energy retrofits measures needed for door(s)
- 5. Candidate discussed specific or general concerns with door replacement
- 6. Candidate identified window operation type(s)
- 7. Candidate identified window frame material(s)
- 8. Candidate identified window glazing type(s)
- 9. Candidate displayed ability to accurately measure a window
- 10. Candidate assessed the orientation of windows and exterior shading
- 11. Candidate assessed and discussed window performance, operation, and general condition
- 12. Candidate identified if repairs to window(s) needed
- 13. Candidate identified if weatherization measures needed for window(s)
- 14. Candidate discussed specific or general concerns with window replacement

Walls

- 1. Candidate identified wall type, including structure and interior/exterior finish
- 2. Candidate identified framing method, or discussed common framing types if test home is not wood-framed
- 3. Candidate determined wall cavity depth
- 4. Candidate identified or discussed infiltration points that impact the pressure boundary
- 5. Candidate determined repairs needed and structural integrity of wall(s) to be insulated
- 6. Candidate determined appropriate R-value of insulation to be added based on conditions and local program requirements

Attic

- 1. Candidate identified and evaluated location of existing thermal boundary and alignment with pressure boundary
- 2. Candidate identified or discussed infiltration points that impact the pressure boundary
- 3. Candidate identified or discussed air sealing sites requiring fire-safe materials and techniques
- 4. Candidate discussed minimum attic ventilation requirements per local code, not specific to test house, including net free area

Attic (con't)

- 5. Candidate identified and evaluated existing attic ventilation
- 6. Candidate determined repairs needed and structural integrity of attic to be insulated
- 7. Candidate determined insulation type and overall effective R-value, considering coverage and conditions
- 8. Candidate determined appropriate insulation R-value to be added based on conditions and local program requirements
- 9. Candidate discussed existing and potential health and safety issues in the attic

Foundation

- 1. Candidate identified the foundation type and material
- 2. Candidate discussed existing and potential health and safety issues in foundation spaces
- 3. Candidate determined if location of existing thermal and pressure boundaries are appropriate or should be changed
- 4. Candidate identified or discussed infiltration points that impact the pressure boundary in foundation spaces
- 5. Candidate identified insulation type, if present, and determined effective insulation R-value; If none present, candidate discussed common foundation insulation types and issues affecting performance
- 6. Candidate determined appropriate insulation R-value to be added based on conditions and local program requirements
- 7. Candidate identified or discussed sources and signs of moisture
- 8. Candidate determined appropriate measures to remediate moisture issues

Mechanical Ventilation and Appliances

- 1. Candidate identified existing ventilation type(s)
- 2. Candidate determined the type of fan control
- 3. Candidate assessed the condition of the ventilation ductwork
- 4. Candidate measured existing flow rate of ventilation fan
- 5. Candidate collected manufacturer's data plate information from one electric appliance
- 6. Candidate evaluated possible refrigerator replacement
- 7. Candidate evaluated possible lighting upgrades
- 8. Candidate identified other sources that contribute to a home's increased electrical consumption
- 9. Candidate discussed water saving opportunities
- 10. Candidate measured or discussed how to measure the flow rate of a showerhead or faucet

Heating, Cooling, and DHW Equipment

- 1. Candidate identified heating / cooling system type(s)
- 2. Candidate identified basic heating / cooling system operating components
- 3. Candidate identified safety features related to heating / cooling appliances

Heating, Cooling, and DHW Equipment (con't)

- 4. Candidate identified or discussed existing heating / cooling system health and safety concerns
- 5. Candidate completed visual inspection of appliance flue system(s) for problems
- 6. Candidate assessed opportunities for heating / cooling system performance enhancements
- 7. Candidate evaluated the distribution system integrity and adequacy
- 8. Candidate assessed opportunities for distribution system insulation
- 9. Candidate evaluated available fuel switching opportunities for heating appliance(s)
- 10. Candidate identified domestic water heating appliance type
- 11. Candidate identified or discussed water heating appliance health and safety concerns
- 12. Candidate identified safety features of domestic water heating appliance
- 13. Candidate determined if current temperature settings pose health & safety and energy concerns
- 14. Candidate identified or discussed opportunities for water heater insulation based on name plate data or manufacturer
- 15. Candidate identified or discussed opportunities for domestic hot water pipe insulation

CAZ Testing

- 1. Candidate set up home for CAZ Testing
- 2. Candidate set up manometer and tubing correctly
- 3. Candidate correctly measured baseline pressure differential
- 4. Candidate turned on exhaust appliances and recorded reading
- 5. Candidate checked air handler impact on CAZ depressurization and recorded reading
- 6. Candidate opened interior door to CAZ and recorded reading
- 7. Candidate identified conditions causing greatest CAZ depressurization
- 8. Candidate checked for spillage in one appliance under greatest CAZ depressurization and stated time limits for spillage testing based on current version of ANSI/BPI-1200
- 9. Candidate determined if the appliance passes the spillage test
- 10. Candidate made appropriate recommendations for the CAZ according to current version of ANSI/BPI-1200

Combustion Safety and Efficiency Testing, and Oven and Stovetop Testing

- 1. Candidate measured CO in the water heater flue gases
- 2. Candidate applied correct action level based on test results for CO in the flue of the water heater, referencing current version of ANSI/BPI-1200
- 3. Candidate measured CO in the heating system flue gases
- 4. Candidate applied correct action level based on test results for CO in the flue of the heating system, referencing current version of ANSI/BPI-1200

Combustion Safety and Efficiency Testing (con't)

- 5. Candidate conducted and evaluated Steady State Efficiency test on heating system
- 6. Candidate measured and evaluated temperature rise in heating system
- 7. (GATED ITEM) Candidate monitored and stated ambient CO levels measured in the CAZ during entire combustion safety testing
- 8. Candidate checked for items, excessive debris inside oven
- 9. Candidate used appropriate sampling location for the oven test
- 10. Candidate applied correct action levels in current version of ANSI/BPI-1200 based on test results for CO in oven
- 11. Candidate inspected stovetop burners for flame quality

Blower Door Testing

- 1. (GATED ITEM) Candidate set combustion appliances to pilot or standby
- 2. Candidate verified solid fuel appliances are in the appropriate condition to allow for blower door testing to be performed
- 3. Candidate set up the blower door frame/shroud/fan correctly
- 4. Candidate set up house correctly in accordance with one of the approved methods listed in current version of ANSI/BPI-1200
- 5. Candidate set up the manometer correctly
- 6. Candidate established baseline pressure differential
- 7. Candidate conducted test to obtain an accurate CFM50 reading
- 8. Candidate interpreted the blower door reading correctly and discussed recommendations
- 9. Candidate measured and evaluated zonal pressure differential to one or two zones (using one-point test)
- 10. Candidate conducted sample room by room inspection with blower door running
- 11. Candidate correctly used pressure pan to evaluate duct leakage
- 12. Candidate discussed how and when to perform a pressurization test

Duct Pressurization Testing

- 1. Candidate demonstrated how to connect duct tester fan to distribution system correctly (do not turn on fan)
- 2. Candidate set up manometer, tubing, and probe correctly for duct testing
- 3. Candidate demonstrated how to seal one duct register
- 4. Candidate discussed procedure for conducting full duct pressurization test
- 5. Candidate discussed applicable standard(s) for interpreting duct tester diagnostic results
- 6. Candidate discussed how to prioritize repairs